

GX Print Server 2 for the Versant™ 180 Press

Fast, easy-to-use print server to boost productivity

SUPERB SPEED AND IMAGE QUALITY

This print server is ideal for professional and corporate offices as well as quick-print environments in which quality and speed are needed to satisfy urgent requests. GX Print Server 2 is powered by Fuji Xerox patented technology to deliver high resolution at high speed and features APPE (Adobe® PDF Print Engine) and CPSI (Configurable PostScript® Interpreter), 1200 x 1200 dpi resolution, 10-bit colour and straightforward spot colour management.

The developed architecture produces an intermediate data format that reduces RIP load while a RIP Accelerator Board maintains image quality through high-speed, lossless compression. In addition, fast serial transmission accelerates processing of heavy image data.

As standard features designed to expand your business, GX Print Server 2 also offers automated RGB colour correction, digital smoothing technology for sharper text and lines, and Color Profile Maker Pro for creating and adjusting CMYK device profiles.

JOB DIRECTOR FOR EFFORTLESS PAGE IMPOSITION AND DOCUMENT CREATION

Manage pages in documents and combine documents with Job Director, which utilises three main functions to give you simple, drag-and-drop control over complex document management tasks: Imposer displays page imposition, pages of the original document and a preview of the finished document. Sequencer allows you to change page order, copy and delete pages, insert blank pages. Create Combined Jobs makes it easy to assemble one document from multiple files created in different applications.

REALISES SMOOTHER GRADATION CORRECTION

The gradation realised by 10-bit rendering is expressed smoother. Additionally, the gradation correction function results in excellent gradation for more natural, smoother reproduction.

EASY, INTUITIVE USER INTERFACE

The user interface ensures fast, easy job setup and operation for any user. Printer functions, job status, error messages and other vital information can be seen at a glance on the print server display. The end result is smoother operation with better accuracy.

SEAMLESS INTEGRATION WITH A VARIETY OF TECHNOLOGIES

GX Print Server 2 for the Versant™ 180 Press provides an excellent collaborative platform to help expand your printing business. The combination with FreeFlow® Digital Workflow Collection automates and maximises your workflow to deliver more job at a shorter turnaround.



GX Print Server 2 for the Versant™ 180 Press

PLATFORM

- Model: A-SV07

KEY FEATURES

- Print Station
 - Main UI software for GX Print Server 2
 - JDF v1.2*
 - Enables GX Print Server 2 integration with JDF workflow
- *For software we support, please contact your local Fuji Xerox representative.
- APPE v3.9 / 4.7
 - Enables GX Print Server 2 to RIP and integrate with PDF workflow
 - Color Profile Maker Pro (CPMP)
 - A colour management feature to create and adjust CMYK device link profiles
 - Job Director - Imposer
 - An imposition layout feature easily operated from Print Station UI
 - Readymade template
 - Job Director - Sequencer
 - A job editing feature with simple, visual UI

- PS Preflight
 - Checks errors or use of inappropriate font or colour
- Raster Image Viewer
 - Displays job preview to edit, adjust curve or brightness
- Warning / Detection
 - Prevent errors when using RGB, spot colour, total ink coverage, hairline and overprint.
- Logical Printer
 - Supports ability to create Hot Folders and logical printers
 - The hot folder relieves the user of the repetitive task of configuring print settings for multiple jobs and allows the direct printing of files without need for an application.
- Security
 - User password control
 - GX Print Server 2 security (log-in) protocol makes shared locations accessible only to authorised users

STANDARD CONFIGURATION

- 23.8" display, keyboard and mouse

OPTIONS

- Ripped PDF Export Kit
- i1Pro 2 Kit
- Stand for GX Print Server


Print Server [GX Print Server 2 for the Versant™ 180 Press]

Item	Description
Type	External
CPU	Intel® Xeon® Processor E3-1275v6 (3.8 GHz)
Storage device	Hard disk : 2 TB (System) + 2 TB x 2 (RAID0), DVD Multi drive
Memory capacity	32 GB (Max : 32 GB)
Server Operation System	Windows® 10 IoT Enterprise (64bit)
Page Description Language	Adobe® PostScript® 3™, PPML, VIPP ¹
Print Data Format	PS, PDF, EPS, TIFF, JPEG
Supported Operating System	Windows® 10 (32bit) Windows® 10 (64bit) Windows® 8.1 (32bit) Windows® 8.1 (64bit) Windows® 7 (32bit) [Service Pack 1] Windows® 7 (64bit) [Service Pack 1] Windows Server® 2016 (64bit) Windows Server® 2012 R2 (64bit) Windows Server® 2012 (64bit) Windows Server® 2008 R2 (64bit) [Service Pack 1] Windows Server® 2008 (32bit) [Service Pack 2] Windows Server® 2008 (64bit) [Service Pack 2]

Item	Description
Supported Operating System	macOS 10.13 High Sierra macOS 10.12 Sierra OS X 10.11 El Capitan OS X 10.10 Yosemite OS X 10.9 Mavericks Mac OS 9.2.2
Interface	Ethernet : 1000BASE-T / 100BASE-TX / 10BASE-T x 2 USB : USB3.0 x 6 , USB2.0 x 2
Network Protocol	TCP/IP(lpd / FTP / IPP ² / SMB / JDF / HTTP), AppleTalk ³ , Bonjour
Power Supply	AC100-240 V +/- 10 % , 3.8 A (100 V) / 1.6 A (240 V), 50/60 Hz common
Maximum Power Consumption	0.4 kW
Dimensions ⁴	W 190 x D 415 x H 365 mm
Weight	11.7 kg

*1: Used with optional software FreeFlow® VI Compose.
*2: Used to work with FreeFlow® Digital Workflow Collection.
*3: AppleTalk is not supported by Mac OS X 10.6 Snow Leopard or later.
*4: Print Server only.

PANTONE® and other Pantone trademarks are the property of Pantone LLC.
All product names and company names mentioned in this brochure are trademarks or registered trademarks of their respective companies.
The product specifications, appearance and other details in this brochure are subject to change without notice for improvements.



For more information or detailed product specification, please call or visit us at

Fuji Xerox (Hong Kong) Limited

11/F Cityplaza 4, 12 Taikoo Wan Road, Quarry Bay, Hong Kong
Tel. 852-2513-2513

<http://www.fujixerox.com.hk/>

